



## Technology the world trusts

Whether you enjoy the thrill of water sports or just relaxing on your boat, choose the engine that helps you get more out of your time on the water.

Every engine in our range uses Yamaha's latest marine technologies, engine layouts and ingenious intake and exhaust systems - and our 4-stroke development has been so successful because, rather than just adapting ordinary automotive engines for the water, we design and build our marine-specification 4-strokes from scratch.

The 15hp is available with electric or manual starting, remote or tiller steering, short or long shaft and power tilt.




- PrimeStart™ system for easy starting
- High-output alternator
- Shallow Water Drive for cruising close inshore
- Fresh Water Flushing system
- One-piece, solid top cowling
- Optimum power-to-weight ratio
- Manual and Electric start options
- Front-mounted shift lever for easy control
- Unique and economical power-to-weight performance
- Power Tilt option
- Light-load manual starter
- Convenient vertical & horizontal storage positions

# Technology the world trusts

If you're looking for the winning combination of easy handling and great control, look no further than the reliable F15.

This versatile, twin-cylinder 4-stroke combines power and responsiveness - and delivers a super-smooth ride. Outstanding fuel economy also means that you're being kinder to the environment, with exhaust emissions cut to a minimum.

Enjoy too, the many extras that only a Yamaha outboard delivers. Benefits like computer-controlled ignition, a special light-load starting system, a water-cooled fuel pump, and a large-volume silencer – all normally only found on larger engines. For commercial, professional or leisure use, it adds up to a winning formula.




### Steering friction

You'll find the 15hp very easy to control and comfortable to drive, thanks to its many features - from the front-mounted shift lever and single-lever steering friction adjuster to the light-load recoil starter. A built-in handle on the steering bracket and resting pads on the rear, make for convenient handling and portability too.




### PrimeStart™

Start your outboard engine as easily as starting a car – even from cold. Exclusive to Yamaha, the PrimeStart™ system ensure that the engine fires first time, every time you engage either the Electric or Manual Start.




### High-output alternator

Never get left short. A High-output alternator ensures that power is always available to start the engine – even after prolonged periods of idling or when you've been running at low revs and using numerous accessories.




### Shallow Water Drive system

Cruise towards the shore with confidence thanks to Yamaha's Shallow Water Drive system. Offering ample protection for your propeller, it allows you to get as close as you need to be, no matter whether you're cruising a murky lake or the crystal clear shallows of the sea.



### 'Start-in-gear' protection

With this kind of power, a false start can be an uncomfortable experience. But Yamaha's 'Start-in-gear' protection eradicates the worry. On Manual Start models, the starter is locked when any gear other than Neutral is engaged. On Electric Start versions, the power supply to the starter motor is isolated until Neutral is selected.



### Fresh Water Flushing system

An easy-access, front-mounted connector allows you to easily flush salt and dirt from the waterways without having to run the engine: just connect a hose and you're ready to go. This is a very efficient way to reduce corrosion and extend the life of your outboard.

<b>Engine</b>	
Engine type	4-stroke
Displacement	362 cm <sup>3</sup>
No. of cylinders/Configuration	2/In-line, SOHC
Bore x stroke	63.0 mm x 58.1 mm
Prop shaft output at mid range	11.0 / 5,500 rpm
Full Throttle Operating Range	5,000 - 6,000 rpm
Lubrication system	Wet sump
Fuel Induction System	1-Carb
Ignition / advance system	CDI
Starter system	Electric (E, EH, EP);Manual (MH) with prime start™
Gear ratio	2.08 (27:13)

<b>Dimensions</b>	
Transom height	S438L:565mm
Fuel tank capacity	separate, 25litres
Oil pan capacity	1.8litres
Weight without propeller	51kg - 60kg

<b>Additional Features</b>	
Control	Tiller handle (MH, EH);Remote control (E, EP)
Trim & Tilt method	Power Tilt (EP);Manual (MH, EH, E)
Light coil / Alternator Output	12V -10Awith rectifier/regulator**
Propeller	Included
Remark	The kW data in this sheet is based on the ICOMIA 28 standard, measured at the prop shaft

All information in this catalogue is given for general guidance only and is subject to change without prior notice. Photographs may show boats being driven by professionals and no recommendation or guidance in respect of safe operation or style of use is intended or implied by the publication of these images. Always respect the local maritime regulations. Always wear the recommended personal flotation device and safety equipment when boating.